

# FLEET DISC SAVER





**50-3955** 1-Ton Dual Wheel 8 X 200mm, 8 X 210mm, 8 X 225mm and 10 X 225mm



**50-3999**MD Rear Adapter 10 X 11.25" and 8 x 275mm



**50-3944** MD Front Adapter 10 X 11.25" and 8 x 275mm



**50-961** Spacers (QTY. 10)



**50-960** Spacers (QTY. 5)



**50-1347** Reach Plate



**50-987** Tapered M22 Nuts (QTY. 5)



**50-032** Feed Screw









LOW MAINTENANCE GEAR BOX

HD T-LOCK CUTTING HEAD



Separate DC spindle speed and feed motors with easy reset over current protection.

# STANDARD FEATURES

## **BENEFIT**

Plug-in, Variable Speed 48V DC Motor ·····	Power to turn bus and truck axles at a wide range of speeds.
Variable Feed Speed ·····	Adjustable feed allows the tech to control the final surface finish.
Performance Plus Cutting Head	Low maintenance and amazing surface finish results.
Low Range Gear Box ·····	Provides 30% more torque than our car lathes.
Adjustable Tool Arms & 190mm Feed Screw ·····	For match-machining the largest rotors in the industry!
Accessories Included ·····	Cutting tips, maintenance tool kit, slide oil, chip deflectors.
4 Wheel, 4 Axis, Adjustable Trolley	Working Range of 18" to 34" allows the use on any low lift or jack stands.
2 YR Parts & Labor Warranty ·····	Match Rotors day in and day out with peace of mind (maintenance & abuse not covered).

## X1 SPECIFICATIONS -

#### PERFORMANCE PLUS CUTTING HEAD

Maximum Rotor Thickness ·····	2.00"
Minimum Rotor Thickness ·····	0.20"
Maximum Rotor Diameter ·····	17.1"
Maximum Friction Face ·····	4.10"
Feed Distance with 50-032 Feed Screw ·····	7.48"

#### **MACHINE**

Spindle Speed ······O-90 rpn
·
Carriage Speed · · · · · Variable
Motor HP ······2 hp peal
Shipping Weight350 lbs
<b>Electrical Supply</b> 90-264VAC 50/60Hz 1ph



\*Pro-Cut's PFM lathes are the first choice of the brake service industry. We have been approved by virtually every auto manufacturer and are considered essential equipment by most 0EM's.

THIS SYSTEM IS SUBJECT TO ONE OR MORE OF U.S. PATENTS: 6,050,160 / 6,101,911 / 6,216,571 / 6,327,947 / 6,330,847 / 6,474,203 / 6,477,928 / 6,895,851 / 5,974,878 / 7,607,377



